




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 6 : A61B 17/80, 17/70</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/56653</p> <p>(43) International Publication Date: 11 November 1999 (11.11.99)</p>
<p>(21) International Application Number: PCT/IB99/00794</p> <p>(22) International Filing Date: 30 April 1999 (30.04.99)</p> <p>(30) Priority Data: 98/05558 30 April 1998 (30.04.98) FR</p> <p>(71) Applicant (for all designated States except US): SOCIETE DE FABRICATION DE MATERIEL ORTHOPEDIQUE (SOFAMOR) [FR/FR]; 13, rue de la Perdrix, F-93290 Tremblay en France (FR).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): ASSAKER, Richard [BE/BE]; 62, rue du Vert Lion, B-7540 Kain (BE). MINFELDE, Richard-Laurent [FR/FR]; 48, rue Raymond du Temple, F-94300 Vincennes (FR). D'AMORE, Jean-François [FR/FR]; 2 bis, rue des Rabouts, F-77144 Montevrain (FR).</p> <p>(74) Agent: MARTIN, Jean-Paul; Cabinet Lavoix, 2, place d'Estienne d'Orves, F-75441 Paris Cedex 09 (FR).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>
<p>(54) Title: BONE PLATE WITH BONE SCREW SECURING MEANS</p> <p>(57) Abstract</p> <p>Implant for the cervical spine comprising an anterior plate (1) for maintaining a bone graft, bone anchorage screws (6, 7, 8) for the plate and means (22) for blocking the screws and preventing any migration of the screws, characterized in that the blocking means comprises at least one slide (22) slidably mounted on the plate so as to be applicable on at least one anchorage screw head (15, 16). The slide cooperates with means (33, 34) for retaining the slide on the head of the screw. The slide may be formed by a thin platelet (22a) which is provided with lateral flanges (25) and is slidable in a complementary cavity (18) provided in the plate (1) while being flush with the surface of the plate (1). The plate (1) includes ramps (26) for retaining the slide (22) on which the flanges (25) are slidable, the slide (22) being slidable to a position in which it at least partly overlaps the heads of the associated screws (6 or 7) and is locked in position by suitable means.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

BONE PLATE WITH BONE SCREW SECURING MEANS

5

TECHNICAL FIELD

The present invention relates to an implant for the spine, and more particularly, but not exclusively relates to an anterior plate for maintaining a bone graft, bone anchorage screws for the plate and means for blocking the screws and preventing any migration of the latter.

10

BACKGROUND

Spinal plates may be introduced from the anterior to stabilize the cervical spine and maintain in position or secure a bone graft which fills the spaces left by the extraction of at least one vertebral disc and, possibly, part of a contiguous cervical vertebra.

15

The bone anchorage screws used for fixing this type of plate in position are either unicortical, and therefore short, since they pass through only the anterior cortical of the vertebra, or bicortical, and therefore long, since they extend through the anterior cortical and the posterior cortical. The short unicortical screws utilize a locking element when there is a possibility the screws may back-out. On the other hand, the long bicortical screws, while less likely to unscrew, have other limitations making them less desirable in certain situations.

20

In practice, the locking element employed up to the present time for unicortical screws is an additional screw which is positioned between two bone anchorage screws and whose head overlaps the heads of these two screws. While there are thin cervical plates without a locking element, the addition of an existing locking element to a given plate design typically results in an increase in plate size, such as the plate's thickness. These additions may also result in a greater plate width than is desirable. Thus, the general desire to further decrease the size of surgical implants indicates a need for new plate and/or locking element arrangements.

30

35

DISCLOSURE OF THE INVENTION

Accordingly, one object of the present invention is to provide a unique device for
5 stabilizing a patient's spine.

Additionally or alternatively, another object of the invention is to provide an
anterior cervical plate provided with antimigration means for the screws arranged in such
manner as to avoid increasing the overall size of the plate.

One form of the present invention is a unique device for stabilizing a patient's
10 spine. In a further form, a slide is incorporated into a spinal plate that may be operable
to serve as a locking element.

According to another form of the invention, a plate has means for blocking the
bone anchorage screws that comprises at least one slide slidably mounted on the plate so
as to be capable of partially covering at least one anchorage screw head, and the slide
15 cooperates with means for retaining it on the head of the screw.

In still another form, the slide is formed by a thin platelet provided with at least
one flange and slidable in a complementary cavity provided on the surface of the plate,
the cavity having a ramp on which the flange can be engaged; the retaining means are
formed by a boss on the plate which clicks into an associated recess when the slide is in
20 its position for blocking and locking the screw. The cavity and the platelet may be so
dimensioned that the surface of the platelet is flush with that of the plate when it is
placed in its cavity. Consequently, for this form, the overall thickness of the anterior
plate may not be increased by the slide.

Further forms, embodiments, objects, aspects and features of the invention will be
25 apparent from the following description and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an elevation view of a cervical spine segment provided with an anterior
5 implant according to the invention for maintaining a bone graft in position.

Figure 2 is a perspective view, to a larger scale, of the anterior plate of Figure 1
provided with a slide for locking two of the screws of the plate.

Figure 3 is a perspective view, similar to Figure 2, showing the plate provided with
two slides and two pairs of bone anchorage screws.

10 Figure 4 is a bottom perspective view, to a larger scale, of one of the screw-
blocking slides for the anterior plate of Figures 1-3.

Figure 5 is a top view to a larger scale of the anterior plate of Figures 1-3 provided
with two screw locking slides, one of these slides being in the locking position, while the
other is in the withdrawn position before locking.

15 Figure 6 is a cross-sectional view taken on line 6-6 of Figure 5.

Figure 7 is a partial cross-sectional view taken on line 7-7 of Figure 3.

MODE(S) FOR CARRYING OUT THE INVENTION

For the purposes of promoting an understanding of the principles of the invention,
5 reference will now be made to the embodiments illustrated in the drawings and specific
language will be used to describe the same. It will nevertheless be understood that no
limitation of the scope of the invention is intended. Any alterations and further
modifications in the illustrated or described embodiments, and any further applications
of the principles of the invention as described or illustrated therein being contemplated as
10 would normally occur to one skilled in the art to which the invention relates.

Shown in Figure 1 is a cervical spine segment C2, C3, C4, C5, and between the
vertebrae C4 and C5 (more usually C4 and C5) of which a bone graft G (partially
visible) is disposed, this graft G being covered by an anterior plate 1 whose function is to
stabilize the spine and to maintain this bone graft G in position.

15 Referring additionally to Figure 2, the plate 1 has an elongate shape with two large
concave sides 2, 3 connected to rounded ends 4, 5, these large sides 2, 3 extend from the
vertebra C4 to the vertebra C5. The plate 1 is provided adjacent to each of its ends 4, 5
with a pair of bone anchorage screws 6, 7 at C4 and C5 which are unicortical and
therefore short, and a central screw 8 which is engaged in an oblong opening 9. Each of
20 the screws 6, 7 extends through a corresponding opening 11, 12 which is of generally
circular section but has a spherical wall 13, 14 acting as a bearing surface for the
corresponding head 15, 16 of screws 6, 7.

Each pair of openings 11 and 12 opens onto a respective cavity 18 provided in the
adjacent surface 1a of the plate 1. Formed in this cavity 18, which in the presently-
25 described embodiment opens onto the opposite faces of the plate 1, is a bridge 19 which
defines at one end a part of the circumference of the openings 11, 12 and extends from
the latter to the opposite wall 21 of the cavity 18. However, the thickness of each bridge
19 is less than that of the plate 1 so that the surface 19a of each bridge 19 is situated
within the cavity 18 at a distance d from the surface 1a of the plate 1 (Figure 2).

30 Each pair of bone anchorage screws 6, and each pair of screws 7, is associated with
a slide 22 for locking screws 6, 7 after anchorage in the vertebral bodies C4, C5,
respectively; and thereby preventing migration of the screws 6, 7. Referring further to
Figures 3 and 4, each slide 22 is formed by a thin platelet 22a whose thickness is at the

most about equal to the distance d between the upper surface 1a of the plate 1 and the surface 19a of the bridge 19. This platelet 22a has an elongate shape whose larger dimension ℓ is just equal to the width of the cavity 18 to allow insertion of the platelet 22a in the latter. Each platelet 22a, not cambered in the free state, is generally slightly
5 cambered in order to make it possible to insert it into its housing cavity 18. This insertion is carried out by positioning it on the bridge 19 and applying a force such that its opposite sides 23 slidably and resiliently bear against the retaining ramps 26. Retaining ramps 26 are each defined along a corresponding one of the opposite sides 24 of cavity 18.

10 Further, each platelet 22a is provided with two lateral flanges 25 which project from the sides 23 under the central part of the platelet 22a. Each of the flanges 25 is adapted to form a shoe 25a slidable along a respective retaining ramp 26 (Figures 2 and 6). The flanges 25 have a width ℓ allowing their insertion in the slots 26a between the sides 24 of the cavity 18 and the opposing sides 20 of the bridge 19, so that their inner
15 faces 27 are placed in sliding contact with the sides 20 of the bridge 19 (Figure 6) when the platelet 22a has been placed in position.

The two large sides 28, 29 of each platelet 22a are concave and the apices 31, 32 of each platelet 22a are rounded so that the rounded apices 31, 32 of the sides 28 close to the screws 6 or 7 are able to partly overlap the heads 15, 16 of the screws 6, 7 when the
20 platelets 22a are in position for locking the screws 6, 7 (Figures 1, 2, 5, 6). Indeed, the openings 11, 12 and the heads 15, 16 are so arranged that, when the screws 6, 7 have been screwed into the vertebral bodies with possibly an inclination in regard to plate 1, their heads 15, 16 have their surfaces in a position in which they are just flush with the underside of the round apices 31, 32.

25 Referring more specifically to Figures 2-6, means are provided for retaining the platelets 22a in their position for locking the screws 6, 7. In the presently-described embodiment, these means comprise, for each platelet 22a, a central boss 33 projecting from the lower face 33a of the platelet 22a, namely that placed in contact with the surface 19a of the support bridge 19, and a corresponding recess 34 provided in the
30 central part of the bridge 19. Thus, when the platelet 22a reaches the position for locking the screws 6, 7; its boss 33 clicks into the recess 34 and maintains the platelet 22a in this position and prevents it from moving forwardly or rearwardly in its cavity 18.

Referring next to Figures 2, 3, 5, and 7, the first thread 36 of the central screw 8 (i.e., the thread closest to its head 37, See Figure 7) is separated from the latter by a smooth part 38. The diameter of this first thread 36 is larger than that of the smooth part 38 and the width e of the oblong opening 9 arranged to receive screw 8 (See Figure 2).

- 5 To place the screw 8 in position, it is therefore necessary to force it through the opening 9 and cause the latter to pass beyond the first thread 36. Thereafter, the latter performs the function of means for retaining screw 8 in plate 1.

- To place the plate 1 and its locking slides 22 in position on the cervical segment such as C4, C5 of Figure 1, the procedure is the following. Referring generally to
10 Figures 1-7, first of all, after the bone graft G has been placed in position in the discal space previously prepared, the surgeon positions the plate 1 equipped with slides 22 and attaches it by means of screws 6 and 7. Afterwards he makes each slide 22 run from the bottom of its housing cavity 18 until flanges 25 come and stop against screws heads 15 and 16. The latter are then partially covered by rounded tops 31, 32 as shown in Figures
15 1, 2, 3, and 5 for at least one of slides 22. When the slides 22 reach this position, in which they partly overlap the heads 15, 16; their respective boss 33 clicks into the respective recess 34 so that each slide 22 is locked in this position in which it locks the associated screws 15, 16 against any migration and therefore against any posterior movement.

- 20 As can be seen in Figure 6, the slides 22 do not project above the surface of the plate 1 owing to their small thickness which is at the maximum equal to about d , and to the provision of a suitable cavity 18. Thus the surface 22b of the slides 22 is generally flush with surface 1a of the plate 1 whose overall thickness is consequently not increased by the presence of the locking slides 22. The locking platelets 22a do not impose to
25 increase the width of the plate 1 in respect to its minimum width such that the same results from the chosen gap between the axis of screws 6 and 7.

- It should be appreciated that the scope of the invention is not intended to be limited to the described embodiments and may encompass variants. For example, boss 33 can be formed on support 19 whilst recess 34 is formed on the platelet 22a. Thus the means
30 33, 34 for blocking the slides 22 in their locking position may be replaced by any other like system. Further, in another arrangement, a slide is associated with each screw and has a single flange that is suitably dimensioned for this purpose. Optionally, the plate may be provided with only a single blocking slide 22, the second pair of screws being for

example associated with other blocking means, or being absent. Moreover, in further embodiments, the implant according to the invention can be used, not only for the cervical spine, but also for other spine segments, for example thoracic and lumbar, and possibly without any bone grafts. Further, in other embodiments, the screw-locking slide
5 and plate arrangement may be used to reduce undesired migration of one or more screws of a type other than the unicortical variety; and may be used to check undesired migration of other types of fasteners used in addition to or as an alternative to one or more screws.

In one alternative embodiment of the present invention, an implant for the spine
10 includes an anterior plate for stabilizing the spine and maintaining a bone graft that has a number of openings, a number of bone anchorage screws for correspondingly engaging the openings of the plate, and means for blocking the screws and preventing any migration of the screws. This implant is further characterized in that the blocking means comprises at least one slide slidably mounted on the plate so as to be capable of partially
15 covering at least one anchorage screw head. This slide cooperates with means for retaining the slide on the head of the screw.

In further embodiment, an implant for the spine includes: a plate for stabilizing the spine that has a number of openings; a number of bone anchorage screws each operable to engage a corresponding one of the openings of the plate; and means for blocking the
20 screws and preventing screw migration. The blocking means includes at least one slide slidably mounted on the plate to selectively cover at least a part of at least one of the screws and means for retaining the slide on at least one of the screws.

In an additional embodiment, an implant for the spine includes: a plate for stabilizing the spine that comprises a number of openings and defines a cavity adjacent at
25 least one of the openings; a number of bone anchorage screws each operable to pass through a corresponding one of the openings of the plate to engage the spine; and a slide slidably mounted in the cavity of the plate. The slide is operable to selectively cover at least a portion of at least one of the screws mounted in at least one of the openings.

While the invention has been illustrated and described in detail in the drawings and
30 foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described and that all changes and modifications that come within the spirit of the invention are desired to be protected.

CLAIMS

What is claimed is:

- 5 1. An implant for the spine comprising: an anterior plate for stabilizing the spine and maintaining a bone graft, the plate having a number of openings, a number of bone anchorage screws for correspondingly engaging the openings of the plate, and means for blocking the screws and preventing any migration of the screws, characterized in that the blocking means comprise at least one slide slidably mounted on the plate so as to be
- 10 capable of partially covering at least one anchorage screw head, and the slide cooperates with means for retaining the slide on the head of the screw.
2. An implant for the spine characterized in that it comprises:
a plate for stabilizing the spine, the plate having a number of openings;
15 a number of bone anchorage screws each operable to engage a corresponding one of the openings of the plate; and
means for blocking the screws and preventing screw migration, the blocking means including at least one slide slidably mounted on the plate to selectively cover at least a part of at least one of the screws and means for retaining the slide on the at least one of
- 20 the screws, the slide cooperating with the retaining means.
3. An implant for the spine characterized in that it comprises:
a plate for stabilizing the spine, the plate including a number of openings and defining a cavity adjacent at least one of the openings;
25 a number of bone anchorage screws each operable to pass through a corresponding one of the openings of the plate to engage the spine; and
a slide slidably mounted in the cavity of the plate, the slide being operable to selectively cover at least a portion of at least one of the screws mounted in the at least one of the openings.
- 30 4. The implant according to claim 1 or 2, characterized in that the retaining means comprises a boss on the slide which is clicked into a corresponding recess defined by a bridge of the plate when the slide is in a position for blocking the screws.

5. The implant according to claim 1 or 2, wherein the plate defines a cavity and the slide is mounted within the cavity.

5 6. The implant according to claim 3, wherein the plate includes a bridge adjacent the slide, and one of the bridge and the slide includes a boss and another of the bridge and the slide includes a recess to correspondingly receive the boss to retain the slide in a screw retaining position.

10 7. The implant according to claim 5 or 6, characterized in that the slide is formed by a platelet including at least one flange, the cavity includes at least one ramp to engage the at least one flange and retain the platelet on the plate.

8. The implant according to claim 7, characterized in that the platelet is provided with
15 two lateral flanges each adapted to slide along a corresponding one of two ramps, the ramps retaining the platelet in the cavity and being formed on opposite sides of the cavity, the platelet being cambered to allow the platelet to be resiliently inserted in the cavity, and the platelet is dimensioned for at least partially overlapping a pair of screw heads each belonging to a corresponding one of the bone anchorage screws.

20

9. The implant according to claim 7 or 8, characterized in that the cavity and the platelet are so dimensioned that the surface of the platelet is generally flush with a surface of the plate when the platelet is placed in the cavity.

25 10. The implant according to any of claims 7-9, characterized in that plate defines another cavity arranged to receive another slide slidably mounted to the plate.

11. The implant according to any of claims 7-10, characterized in that the cavity communicates with a pair of the openings of the plate.

30

12. The implant according to any of claims 10-11, wherein a central part of the plate defines a central opening and further comprising a selected bone anchorage screw to pass through the central opening, the selected bone anchorage screw including a first thread

and a screw head, the first thread being separated from the screw head by a generally smooth part, the first thread having a diameter larger than the width of the screw passage opening for preventing the return of the selected bone anchorage screw after the bone anchorage screw is inserted in through the central opening.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 7




FIG. 5

INTERNATIONAL SEARCH REPORT

In International Application No

PCT/IB 99/00794

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61B17/80 A61B17/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 423 826 A (LOWERY GARY L ET AL) 13 June 1995 (1995-06-13) column 27, line 46 - line 62; figure 2 ----	1-3
A	US 5 616 144 A (YAPP RONALD A ET AL) 1 April 1997 (1997-04-01) column 4, line 43 - line 67 ----	1-3
A	EP 0 705 572 A (SYNTHESE AG) 10 April 1996 (1996-04-10) -----	

☐

Further documents are listed in the continuation of box C.

☒

Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

7 July 1999

Date of mailing of the international search report

14/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gérard, B

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 99/00794

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5423826 A	13-06-1995	US 5364399 A	15-11-1994
		AU 679587 B	03-07-1997
		AU 8125594 A	22-05-1995
		CA 2172369 A	04-05-1995
		CN 1138291 A	18-12-1996
		EP 0744920 A	04-12-1996
		JP 9504213 T	28-04-1997
		WO 9511632 A	04-05-1995
		AU 692147 B	04-06-1998
		AU 6094894 A	29-08-1994
		CA 2154470 A	18-08-1994
		CN 1119411 A	27-03-1996
		EP 0683646 A	29-11-1995
		JP 8506502 T	16-07-1996
		TR 28594 A	01-11-1996
		WO 9417744 A	18-08-1994
		ZA 9400777 A	08-09-1994
US 5616144 A	01-04-1997	BR 9304828 A	16-08-1994
		CA 2109907 A	26-05-1994
		DE 69320593 D	01-10-1998
		DE 69320593 T	04-03-1999
		EP 0599640 A	01-06-1994
		ES 2124288 T	01-02-1999
		JP 6277228 A	04-10-1994
		US 5549612 A	27-08-1996
EP 0705572 A	10-04-1996	US 5601553 A	11-02-1997
		CA 2146679 A	04-04-1996
		JP 8206143 A	13-08-1996